

PSR® is formulated to remove residues caused by fresh water including scale, silicate, calcium, sludge, and all other mineral deposits.

Originally designed to address problems within municipal drinking water systems, **PSR®** has been formulated to meet strict NSF requirements.

PSR® rids your potable water system of odors & discoloration by attacking the source! Scale builds on low lying, flat sections of your system allowing bacteria to form. **PSR®** targets & removes these areas, bringing new life to your fresh water system.

Built on our proven formula providing a safe, non-toxic solution, **PSR®** takes it one step further by employing only food-grade rated chemicals. Thus ensuring your system will remain safe for drinking.

PSR® provides impeccable results without having to remove any piping or create a mess.

PSR® can be used by one of two methods;

- **Immersion:** Isolate the tanks, fill the entire system and let stand
- **Circulation:** Inject **PSR®** into tank, mix, run faucets for 2 min. every 15 min until the tank is empty, fill the system and rinse.



PSR® is sold in concentrated form. One gallon of PSR® will treat approximately 30 to 40 gallons of potable water.
 (depending on dilution rates)

SAFETY

- **PSR®** is safe for the users, equipment and the environment.
- **PSR®** will not harm the properties of most surfaces including, plastic, metal, rubber, fiberglass, vinyl, wood, or paint.
- Care should be given when **PSR®** is used with zinc based metals such as zinc anodes, tin, or galvanized materials.
- **PSR®** is biodegradable & can be disposed through regular sewer systems.
- **PSR®** passed the California Fish Toxicity Assay Test, Department of Hazardous Substances (Title 22) and complies with NSF International standard 60.
- Based on current EPA guidelines, **PSR®** is classified as non-flammable and meets all requirements regarding hazardous and dangerous materials.

Availability

1 gallon , 5 gallon pail, 55 gallon drum
 or a 250 gallon tote tank

Pipe gallonage chart

| Diameter | Length in feet | | | |
|---------------|----------------|------|-----|-----|
| | 1 | 5 | 10 | 20 |
| Inches | | | | |
| 1 | 0.04 | 0.2 | 0.4 | 0.8 |
| 2 | 0.16 | 0.8 | 1.6 | 3.2 |
| 3 | 0.37 | 1.84 | 4 | 8 |
| 4 | 0.65 | 3.26 | 7 | 13 |
| 5 | 1.02 | 5 | 10 | 20 |
| 6 | 1.47 | 7 | 15 | 29 |
| 7 | 2 | 10 | 20 | 40 |
| 8 | 2.61 | 13 | 26 | 52 |
| 9 | 3.31 | 16 | 33 | 66 |
| 10 | 4 | 20 | 41 | 82 |
| 12 | 6 | 29 | 59 | 118 |
| 14 | 8 | 40 | 80 | 160 |
| 16 | 10 | 52 | 104 | 208 |

FAST SAFE NON-TOXIC BIODEGRADABLE NON CORROSIVE NON HAZARDOUS

Dealer/Distributor Label

TRAC Ecological
 1103 Old Griffin Road, Ft. Lauderdale, FL 33004 USA
 001.954.987.2722 Voice ~ 001.954.583.4933 Fax
 www.TRAC-online.com ~ Info@TRAC-online.com