

Designed for applications ranging from 10 to 40 Gallons
 small to medium air conditioning & refrigeration plants ~ main & auxiliary
 engines up to 1800 horsepower small to medium size black water systems ~
 heat exchangers up to 40 gallons piping systems to 3" diameter

Trac Ecological's advanced descaling systems provide an environmental answer to internal, in-place cleaning, of all your vital onboard equipment!

We designed the YACHT-FLUSH® to be a compact yet powerful tool built right into a rugged fifteen gallon tank! Combining two of our most successful flushing units in one, the YACHT-FLUSH® has been specifically designed with large yachts in mind. The YACHT-FLUSH® can handle large cleaning applications all while remaining small and compact enough for easy onboard storage.

YACHT-FLUSH® provides portability and versatility while still efficiently handling small to medium size engines, heat exchangers, air conditioning & refrigeration systems. Use the YACHT-FLUSH® with any of our safe & biodegradable descalers for unparalleled cleaning results.

This unit will save time and money by providing a welcomed alternative to mechanical cleaning. The YACHT-FLUSH® will allow you to clean a system in place and have it back in service in a fraction of the time!

Trac's YACHT-FLUSH® is an essential tool to anyone responsible for water system maintenance!

Specifications

- Anti-corrosive 1" centrifugal RULE pump, 110V,46.6GPM @ 25PSI.
- All plumbing fitted in high strength schedule 80 PVC.
- Pump designed for easy removal for maintenance.
- 15 G. open head tank made of recycled plastic.
- Isolation valves to allow for easy maintenance.

Applications

- All Generators
- Heat exchangers
- Chiller plants to 90 tons
- Main Engines to 3000 HP
- Small Black water systems
- Piping systems and Seachests

Available Equipment

- YACHT-FLUSH® 110 volt AC - part number 1270
- YACHT-FLUSH® 220 volt AC - part number 1270-E



The YACHT-FLUSH® has been designed for use with any of Trac's environmentally friendly products. Careful attention has been given to ensure safety of both you and your equipment.

Yacht-Flush		Specifications
max flow	gpm	46.6
	lpm	176.6
max head	ft.	12
	m	3.6
supply		1"
return		1"
hp		0.23
kw		0.175
watts		175
volts	us	110
	euro	n/a
type		sub
weight	lbs.	17.4
	kg.	7.9
length	in.	20.5
	cm	52
width	in.	12
	cm	30.48
height	in.	26.5
	cm	67.3