

PSR® is formulated to remove residues caused by fresh water including scale, silicate, calcium, sludge, and all other mineral deposits.

PSR® rids your potable water system of odors & discoloration by attacking the source! Scale builds on low lying, flat sections of your system allowing bacteria to form. PSR® targets & removes these areas, bringing new life to your fresh water system.

PSR® provides impeccable results without having to remove any piping or create a mess.

PSR® can be used by one of two methods:

- Immersion: Isolate the tanks, fill the entire system and let stand
- Circulation: Inject PSR® into tank, mix, run faucets for 2 min. every 15 min until the tank is empty, fill the system and rinse.



PSR® is sold in concentrated form. One gallon of PSR® will treat approximately 30 to 40 gallons of potable water. (depending on dilution rates)

Safety

- PSR® is safe for the users, equipment and the environment.
- PSR® will not harm the properties of most surfaces including, plastic, metal, rubber, fiberglass, vinyl, wood, or paint.
- Care should be given when PSR® is used with zinc based metals such as zinc anodes, tin, or galvanized materials.
- PSR® is biodegradable & can be disposed of in accordance with local regulations.
- Based on current EPA guidelines, PSR® is classified as non-flammable and meets all requirements regarding hazardous and dangerous materials.

Availability

- 1 gallon
- 5 gallon pail
- 55 gallon drum
- 250 gallon tote tank

Pipe gallonage chart

Diameter Inches	Length in feet			
	1	5	10	20
1	0.04	0.2	0.4	0.8
2	0.16	0.8	1.6	3.2
3	0.37	1.84	4	8
4	0.65	3.26	7	13
5	1.02	5	10	20
6	1.47	7	15	29
7	2	10	20	40
8	2.61	13	26	52
9	3.31	16	33	66
10	4	20	41	82
12	6	29	59	118
14	8	40	80	160
16	10	52	104	208